System SF50 H-S-W



☐ Inquiry ☐ Order	Customer number:
Company stamp / address:	Contact person:
	Telephone:
	Quotation No.:
	Commission:
Number of systems:	
Opening direction: inwards opening outwards opening	ng (Note: Use interior view!)
Parking bay: Typ 1 Typ 2 Typ 3	Special solution
Number of panel: to the left to the right (Please draw a floor plan or a view sketch for better understanding)	
Dimensions: Width: (Total unfolding)	Height: (incl. possible floor recession)
Colour: RAL 7016 RAL 9006 RAL 9007 RAL 9016 E6-EV1 Special colour Pre anodizing	
Handle colour: E6-EV1 powder RAL 903	11 mat RAL 9016 Special colour
Handle height: H = (Indicate handle height from lower panel edge)	
Glazing: Standard Insulated glass 2 x 4/20 cavity Ug 3.0 without glass: prepared for mm Special glass: (Please indicate exact designation)	
Ceiling connection: without overlay profile with overlay profile inside with overlay profile outside	
Ground connection: with floor sockets with flush bottom track (height incl. floor recession) with recessed bottom track and lowerable bottom door seal (height incl. floor recession)	
Locking of turn panel: Standard (shoot bolt lock operated from inside only) Shoot bolt-lock with PZ (operated from both sides) Mortise door lock with PZ (operated from both sides) Roller latch + 2 x dead lock + HEWI push handle Anti-draft lock with mushroom-lock, latch and PZ (operated from both sides) other:	
Turn panel: without Integrated turn-panel in panel-No.: with overhead door closer, push handle, 2 x dead lock with mortise door lock with PZ and handle at both sides (The panel No. is counted from the left to the right. Please draw opening direction into the sketch.)	

Please enclose floor plan resp. view sketch and remarks (please use inside view)