## System SF55 H-S-W

## **SUNFLEX**

🗆 Inquiry 🔲 Order	Customer number:
Company stamp / address:	Contact person:
	Telephone:
	Quotation No.:
	Commission:
Number of systems:	
Opening direction: inwards opening outwards opening (Note: Use interior view!)	
Parking bay:       Typ 1       Typ 2       Typ 3	Special solution
Number of panel:	
Dimensions: Width: (Total unfolding)	Height: (incl. possible floor recession)
Colour:     RAL 7016     RAL 9006     RAL 9007     RAL 9016     E6-EV1     Special colour       Pre anodizing	
Handle colour: E6-EV1 powder RAL 901	.1 mat 🗌 RAL 9016 🗌 Special colour
Handle height: H = (Indicate handle height from lower panel edge)	
Glazing:     Standard Insulated glass 2 x 4/20 cavity Ug 1.1       without glass: prepared for mm       Special glass: (Please indicate exact designation)	
<b>Ceiling connection:</b> without overlay profile with ov	erlay profile inside 🛛 with overlay profile outside
Ground connection: with floor sockets with flush bottom track (height incl. floor recession) with recessed bottom track and lowerable bottom door seal (height incl. floor recession)	
Locking of turn panel:     Standard (shoot bolt lock operated from inside only)       Shoot bolt-lock with PZ (operated from both sides)     Mortise door lock with PZ (operated from both sides)       Roller latch + 2 x dead lock + HEWI push handle     Anti-draft lock with mushroom-lock, latch and PZ (operated from both sides)       other:	
	, push handle, 2 x dead lock h PZ and handle at both sides ft to the right.

Please enclose floor plan resp. view sketch and remarks (please use inside view)