## System SF75c



🗌 Inquiry 🔲 Order	Customer number:
Company stamp / address:	Contact person:
	Telephone:
	Quotation No.:
	Commission:
Type of timber and finish:	
Number of systems:	
Opening direction: inwards folding outwards folding (Note: Use interior view!)	
Number of panel to the left to the right	(Please draw a floor plan or a view sketch for better understanding)
Dimensions: Width: (Total unfolding)	Height: (incl. possible floor recession)
Timber design:	
<b>Colour:</b> RAL 7016 RAL 9006 RAL 9007	RAL 9016 E6-EV1 Special colour   Pre anodizing
Colour of hinges: E6-EV1 powder RA	L 9011 mat 🔲 RAL 9016 🔲 Special colour
Handle colour: E6-EV1 powder RA	L 9011 mat RAL 9016 Special colour
Handle height: H = (Indicate handle height from lower panel edge)	
Glazing: Standard heat protection glas without glass: prepared for Special glass:	mm
Floor connection:     image: with weathered bottom track       image: im	
with flush bottom track (height incl. floor recession)	
with recessed bottom track ar	nd lowerable bottom door seal (height including recess)
Locking of turn panel:     Standard (shoot bolt lock ope       Shoot bolt lock with PZ (opera       Roller latch + 2 x dead lock +       Anti-draft lock with mushroo       latch and profile cylinder (operation)       Pull handle for turn panel, ou       other:	Ited from both sides) HEWI push handle m head and 4 point locking, erable on both sides) Itward folding system
Additional safety: Twin-Lock WK2-Safety package	

Please enclose floor plan resp. view sketch and remarks (please use inside view)